

EJ-701DR

Diversity receiver, 16 channels, 863-865MHz



Features

- Range up to 100 m free field
- Digital display for channels (lit when changing)
- Wireless receiver for 1 microphone
- Diversity reception
- ½ width 19" rack mountable
- The receiver is connected to the existing sound system and/or to a hearing loop driver.

EJ-701DR is a diversity receiver included in OKAYO wireless microphone system. It can be used with 1 wireless microphone and be connected to existing sound systems and/or an induction loop driver.

OKAYO II modular, microphone system range

In addition to the EJ-701DR, the OKAYO II modular microphone system range includes push to talk microphones, body pack transmitters with a range of microphone options, body pack receivers, and rechargeable powered speakers with built in receivers.

With this wide range of options, the OKAYO II wireless microphone system is uniquely flexible and can be easily configured for different applications. It is equally suitable for use in schools, seminars, meetings, places of worship, product demonstrations, aerobics classes and guided tours.

Univox – co-developed with OKAYO

Univox and Okayo have co-developed body pack transmitters and receivers to improve speech intelligibility for hearing aid users. To comply with accessibility requirements and provide a good audio experience even for the hearing impaired, make sure you use these special developed products.

Specifications

Technical data - general

PLL-receivers and transmitters

Carrier frequency	863-865 MHz, other frequencies on demand
Channels	16 (frequency dependant)
Wireless coverage	up to 100 m in free field
LCD display	channel, frequency, battery status
Tuning	set, up, down
Frequency modulation	Max. 12 MHz
Frequency deviation	80 kHz, level control
Dynamic range	110 dB
T.H.D	<1%
Pre-emphasis	<50 µS
Noise Gate	Tone key
Frequency response	70 Hz - 17 KHz

Technical data – EJ-701DR

Audio output	6,3mm (mixer) balanced XLR
Output level	Mixer out: low 80mV/high 700mV CH-out: 80mV
Power supply	AC 100-240V/DC 12V, 1A switched power supply
Weight	1.2kg
Dimensions (DxWxH)	210x215x44mm
Art. No.	506701



Diversity receiver EJ-701DR



Diversity receiver EJ-702DR Plus



Diversity receiver EJ-704DR



For complete manual and system components, please refer to univox.eu.