



## EJ-702DR Plus

Twin diversity receiver, 16 channels,  
863-865MHz

### Features

---

- 1 duo-receiver, for use with 2 wireless microphones
- Wireless coverage up to 90 m
- Digital display
- Diversity reception
- ½ width 19" rack mountable
- The receiver is connected to the existing sound system and/or to a hearing loop driver.

### Okayo Modular Microphone System Range - flexibility

The EJ-702DR Plus twin wireless receiver is part of the Okayo modular wireless system range. By integrating 2 receivers in the same module with a shared interface, this cleverly designed unit offers the same functionality as a conventional 2 channel receiver. It can be used with two wireless microphones on separate channels, each benefiting from the high frequency operation and diversity reception to deliver high quality audio with low distortion, low noise and reduced susceptibility to interference. By adding a second EJ-702DR Plus a maximum of four wireless microphones can be used simultaneously.

The system is available for operation at different frequencies in the range from 514MHz up to 865MHz. Please contact us to discuss your requirements.

### Okayo modular, microphone system range

In addition to the EJ-702DR Plus, the Okayo modular microphone system range includes push to talk microphones, body pack transmitters with a range of microphone options, body pack receivers, and rechargeable powered speakers with built in receivers.

With this wide range of options, the Okayo wireless microphone system is uniquely flexible and can be easily configured for different applications. It is equally suitable for use in schools, seminars, meetings, places of worship, product demonstrations, aerobics classes and guided tours.

### Univox – co-developed with Okayo

---

Univox and Okayo have co-developed a number of Okayos standard products, for example body pack transmitters and receivers, to improve speech intelligibility for hearing aid users. To comply with accessibility requirements and provide a good audio experience even for the hearing impaired, make sure you use these special developed products.

## Specifications

---

### EJ-702DR Plus, Twin Diversity receiver

2 x 16 channel receivers

Carrier frequency	863-865 MHz, other frequencies on demand	
Channels	16 (frequency dependant)	
Wireless coverage	60-90 m	
LCD window	channel, reception strength	
Channel adjustment	frequency set, up/down	
Frequency modulation	max. 24 MHz	
Dynamic range	110 dB	
T.H.D	<0.5 %	
Pre-emphasis	<50 $\mu$ S	
Silent mode	tone key and noise lock dual-squelch, to eliminate external noise	
Frequency response	70 Hz - 17 KHz	
Audio output	6.3 mm (mixer)	XLR balanced
Output level	Hi: 730mV/2k $\Omega$	1V/600 $\Omega$
	Low: 80mV/2k $\Omega$	
Power supply	AC switching power adapter 100 ~ 240V, 12 ~ 15V/0.6A	
Weight	1.2 kg	
Dimensions (DxWxH)	210 x 215 x 44mm	
Art. No.	506712	



For complete manual and system components, please refer to [univox.eu](http://univox.eu).

